

## مواصفات لوح الجلو ميرا - جودة وأمان في كل تفاصيله

The panel is made of Finger Joint blockboard  
Kiln-dried wood, treated against moisture and bacteria

Thickness: 18 mm  
Panel size: 122 x 275 cm

Both sides: Same color, PET material

Features:

Eco-friendly and odor-free

High resistance to scratches and moisture

اللوح مصنوع من كونتر تجميع Finger Joint خشب مجفف ومعالج ضد الرطوبة والبكتيريا

التخانة : 18 مم

مقاس اللوح : 275\*122

الوجوهين : نفس اللون من خامة PET

يتميز اللوح بأنه

1- صديق للبيئة و خالي من الروائح.

2- مقاومة عالية للخدش و ضد الرطوبة.

3- درجة عالية من اللمعان.

# Technical Specs DATA SHEET

Section	Item	Details
Product Name		PET Solid Wood Board – 18 mm thickness
1. Product Structure	Core	Selected Pine Solid Wood
	Top Surface	Decorative PET Film – 0.70 mm
	Bottom Surface	PET Balancing Film – 0.35 mm
	Reinforced Layer	Eucalyptus-Poplar Plywood – 2.75 mm (reinforced plywood)
2. Standard Specifications	Thickness	18 mm
	Size	2750 x 1220 mm
	Density	730 ± 20 kg/m³
	Moisture Content	6 – 10 %
3. Physical Properties	Bending Strength	45 MPa
	Bonding Strength	≥ 1.2 MPa
	Surface Hardness	3 S
	Screw-Holding Capacity	1200 N
	Dimensional Stability	Excellent
4. Key Features	High-Gloss, Scratch-Resistant PET Finish	High-gloss PET finish with scratch resistance
	Moisture-Proof & Heat-Resistant	Resistant to moisture and heat
	Odor-Free, Eco-Friendly	Environment-friendly and odor-free
	Enhanced Stability with Reinforced Plywood	Improved stability with reinforced plywood layer
5. Applications	Premium Furniture	High-end / premium furniture
	Kitchen Cabinets	Kitchen cabinetry
	Wardrobe Doors	Wardrobe / closet doors
	Interior Decoration	Interior décor and wall applications

621 S-HG

631-SM

622 S-HG

632-SM

623 S-HG

633-SM

625 S-HG

635-SM

626 S-HG

636-SM

624 S-HG

634-SM

627 S-HG

637-SM

628 S-HG

638-SM

629 S-HG

629-SM

611 S-HG

611-SM

641 S-HG

641-SM

620 S-HG

620-SM